

Contents

One-Dimensional Arrays	1
Multiple Choices	1
Exercises	2
Syntax	2
Displaying Arrays	3
Filling Arrays	4
Looking For Values	4
Manipulating Two Arrays	5
Methods	5
Simple Algorithms	5
Problems on Binary Search	6
Wrap-Up Problems	8

One-Dimensional Arrays

Solutions for those exercises.

Multiple Choices

1. What is the correct way of creating an array of `int` of size 5 named `myArray`?

- ☐ `int[] myArray = new int[5];`
- ☐ `int[] myArray = int[5];`
- ☐ `int[5] myArray = new int[];`
- ☐ `int[4] myArray = new int[];`
- ☐ `int myArray = new int[5];`
- ☐ `int[] myArray = new int[4];`
- ☐ `int[] myArray = new int(5);`
- ☐ `int[] myArray = int[4];`

2. Consider the following code:

```
int[] grades = {10, 20, 5, 15};  
Console.WriteLine(grades[2]);
```

What will it display?

- ☐ 5
- ☐ Nothing
- ☐ 20
- ☐ 15
- ☐ grades
- ☐ grades(2)

☐ 10

3. In the following statement, the value 5 is called the...

```
string[] names = new string[5];
```

- ☐ allocation limit
- ☐ size declarator
- ☐ length
- ☐ upper bound

4. Each element in an array is assigned a unique number called the...

- ☐ subscript
- ☐ index
- ☐ position
- ☐ rank

5. Consider the following code:

```
char[] grades = {'A', 'B', 'C', 'D', 'F'};
int i = 0;
while(i < grades.Length){
    i++;
    Console.WriteLine(grades[i]);
}
```

Something is wrong with it, can you tell what?

- ☐ There will be an "Index was outside the bounds of the array." error.
- ☐ The array is not properly initialized.
- ☐ The loop is infinite
- ☐ grades.Length is not declared.

Exercises

Syntax

1. Write a statement that creates a 10-element `int` array named `numbers`.
2. Write a statement that creates and initializes an array of `double` with the values 12.5, 89.0 and 3.24.
3. In the following, what is the value of the size declarator? What is the value of the index?

```
int[] numbers;
numbers = new int[8];
numbers[4] = 9;
```

4. What is "array bounds checking"? When does it happen?
5. Is there an error with the following code? If you think there is one, explain it, otherwise draw the content of the `myIncomes` array once those statements have been executed.

```
double[] myIncomes = new double[5];
myIncomes[1] = 3.5;
// No income on day two.
myIncomes[3] = 5.8;
myIncomes[4] = 0.5;
myIncomes[5] = 1.5;
```

6. What would be the size of the `test` array after the following statement has been executed?

```
int[] test = {3, 5, 7, 0, 9};
```

7. What is wrong with the following array declaration?

```
int[] books = new int[-1];
```

8. Suppose we have an array named `temp` that has been declared and initialized. How can we know the number of elements in this array?

9. What is the value of `count` and the content of `number` once the following has been executed?

```
int count=2;
int[] number={3, 5, 7};
number[count--] = 8;
number[count]--;
```

10. Describe what the following code would do.

```
int[] record = { 3, 8, 11 };
int accumulator = 0;
foreach (int i in record)
    accumulator += i;
```

Displaying Arrays

1. Write code that displays the first and last element of an array.
2. What will be displayed at the screen by the following code?

```
int[] values = new int[6];
for (int i = 0 ; i < 6 ; i++)
    values[i] = (i * 2 );
```

```
foreach (int j in values)
    Console.WriteLine(j);
```

3. Suppose we are given an `int` array `dailyPushUp` with 7 elements. Write a piece of code that displays the value of the elements stored in the array `dailyPushUp`.
4. Write code that displays every element in a `numbers` array of integers.
5. Write code that displays every element in a `numbers` array of integers in reverse order.
6. Write code that displays every other element in a `numbers` array of integers (that is, every even index).
7. Given an array `numbers` and a variable `x`, write code that displays every value in `myArray` that is equal to or greater than `x`.
8. Write code that displays every unique value of *a sorted* array `numbers`. This array could contain, for example, 1, 1, 1, 4, 4, 5, 8, 9, 11: values are increasing and can occur multiple times. In our example, the values 1, 4, 5, 8, 9 and 11.

Filling Arrays

1. Given an array `myArray` and some value `x`, write code that sets the value of every array element to `x`.
2. Given some positive number `n`, write code that first declares an array of length `n`, then sets its contents to sequentially increasing values 1, 2, 3, ..., `n`.
3. Given an array of integers, and two integer variables `oldValue` and `newValue`; write code that replaces every occurrence of `oldValue` in the array with `newValue`.
4. Write code that squares every value in an `myArray` integer array. For example, an array containing 2, 3, 4 would after the program contain 4, 9, 16.

Looking For Values

1. Given an array `myArray` and a value `val`, write code that checks if `myArray` contains `val`. The result should be `true` if `val` occur in `myArray` and `false` otherwise.
2. Given an array `myArray` and a variable `x`, write code that computes the number of times `x` occurs in `myArray`.

3. Given an array `myArray` and two values `x` and `y`, write code that checks if `myArray` contains *either* `x` or `y`. The result should be **true** if `x` or `y` occur in `myArray` and **false** otherwise.
4. Given an array `myArray` and two values `x` and `y`, write code that checks if `myArray` contains *both* values `x` and `y`. The result should be **true** when both values occur and **false** otherwise.
5. Given an integer `myArray` and a strictly positive integer value `x`, find an array element whose value is largest while also being strictly less than `x` and display it, or display 0 if there is no such value. For example, in an array containing 1, 2, 6, 7, 3, 9 with `x` being 8, the solution is 7.
6. Consider an array of **char**. Implement code to check if the array values form a palindrome, i.e., it reads the same way forwards and backwards.

Manipulating Two Arrays

1. Assuming we have two **int** arrays of the same size, `firstA` and `secondA`, write a program that copies the content of `firstA` into `secondA`.
2. Given two arrays `array1` and `array2`, write a program to determine if there exists a value that occurs in both arrays. If such value exists, the result should be **true** and **false** otherwise.
3. Write a program that combines two **string** arrays called `array1` and `array2` into a single array containing first all the elements from `array1`, then all the elements from `array2`.
4. Given two arrays `arrayA` and `arrayB`, write code to check if every element in `arrayB` occurs in `arrayA`, then display the result as **true** or **false**.

Methods

1. Write a static method (header included) that takes as an argument an **int** array, and displays on the screen the value of each element of that array.
2. Write a static method (header included) that takes as an argument an **int** array, and stores the value 10 in each element of that array.

Simple Algorithms

1. Write a program that computes the sum of values stored in a numbers array of integers and displays it.

2. Given an array of positive integers, count how many even values occur in that array.
3. Write a program that computes the average of the elements in a `arrayP` numeric array.
4. Write a program that finds the largest value in an integer array `arrayP`.
5. Write a program that finds the smallest value in an integer array `arrayP`.
6. Write a program that finds the *second* smallest value in an array of integers `arrayP`.
7. Write code that finds the index of the first occurrence of a value `val` in an array `arrayP`. If the array does not contain the value, the result should be -1.
8. Write code that finds the index of the last occurrence of a value in an array. If the array does not contain the value, the result should be -1.
9. Write code to reverse the contents of an array `myArray`. For example, an array containing 1, 4, 3, 2, 5 should contain, after the program was executed, 5, 2, 3, 4, 1.

Problems on Binary Search

Those two problems are related to binary search.

1. Assume `arrayEx` is an array of `int` containing the following values:

```
int[] arrayEx =  
{  
    10,  
    15,  
    30,  
    45,  
    60,  
    75,  
    90,  
    105,  
    120,  
    135,  
    150,  
    165,  
    180,  
};
```

and consider the following algorithm:

```

bool fsf = false;
int tar = 105;
int sta = 0;
int end = arrayEx.Length - 1;
int mid,
    cur;
while (sta <= end && !fsf)
{
    mid = (sta + end) / 2;
    cur = arrayEx[mid];
    if (tar == cur)
    {
        fsf = true;
    }
    else if (tar > cur)
    {
        sta = mid + 1;
    }
    else
    {
        end = mid - 1;
    }
}

```

Complete the following table, giving the value of `sta`, `end`, `mid`, `fsf` and `cur` before the **while** loop is executed, after it has executed one time, two times, etc. If the value is not set at this point, write “undef”, and if the loop stops before the Xth iteration, simply cross out the Xth iteration. Report the value even if it did not change.

	Before loop	After 1 iteration	After 2 iterations	After 3 iterations	After 4 iterations
sta					
end					
mid					
fsf					
cur					

2. Consider the following **incorrect** implementation of binary search:

```

int[] arrayP = {10, 15, 30, 45, 60, 75, 90, 105, 120,
    ↪ 135, 150, 165};
bool fsf = false;
int tar = 165;

```

// Found target so far?
// Target to find.

```

int sta = 0; // Beginning
int end = arrayP.Length - 1; // End
Console.WriteLine($"Starting ({sta}-{end})");
while (sta <= end && !fsf){ // Here goes the main
    ↪ loop
    if (tar < arrayP[(sta + end) / 2]) { end = (sta +
        ↪ end) / 2;
        Console.WriteLine($"Going left
    ↪ ({sta}-{end})"); }
    else if (tar == arrayP[(sta + end) / 2]) fsf = true;
    else { sta = (sta + end) / 2;
        Console.WriteLine($"Going right
    ↪ ({sta}-{end})"); }
}
Console.WriteLine("Found: " + fsf);

```

- (a) Indicate what would be displayed
- (b) Explain why this implementation is incorrect, and how it can be fixed.

Wrap-Up Problems

1. Declare and initialize three arrays:
 - Choose different data type for each array,
 - Make the arrays have different lengths: 3, 5, 10 elements respectively,
 - Initialize each array with appropriate values of your choice (depends on the type).

After you have declared and initialized the arrays, display on the screen

 - The first value from array 1 (0th index),
 - The last value from array 2 (4th index),
 - The first three values from array 3 (indexed 0 - 2).
2. Suppose given two 1-dimensional arrays of `char` called `passcode` and `codeentered` of the same size.
 - (a) Write a program that displays "Passcode correct" if the content of `passcode` and of `codeentered` are identical.
 - (b) Write a program that displays "Passcode valid" if `passcode` does not contain the same character twice.
 - (c) Write a program that displays "Passcode sorted" if `passcode` is sorted (either in ascending or descending order).
 - (d) Write a program that displays the number of matching characters in the same position in both arrays. For example, if

passcode contains b, C, 4, a and codeentered contains B, 4, c, a, then "1" should be displayed, as only one character (a) is in both arrays at the same position.

- (e) Write a program that displays the number of matching characters in both arrays. For example, if passcode and codeentered are as in the previous question, then "2" should be displayed, as two characters (4 and a) are in both arrays¹.

3. Consider this array of words:

```
string[] words = { "voice",  
                  "effect",  
                  "day",  
                  "orange",  
                  "appliance",  
                  "fly",  
                  "cloud",  
                  "degree",  
                  "engine",  
                  "society"};
```

Write code to display an answer to the following questions. If the solution requires looping, use **foreach** loop when possible. Otherwise, use a **for** loop.

- (a) Does words array contain "engine"? (true/false)
- (b) Does words array contain "day" at least 2 times? (true/false)
- (c) What is the position (index) of the word "society"? If it does not exist answer should be -1. Find the position of the first occurrence in case there are multiple matches.

After you have implemented your code, change the array contents and make sure your code still works and does not crash.

Here is another array of words to test your solution:

```
string[] words = {"addition", "day", "start", "dock",  
                  "fowl", "fish", "seat", "day"};
```

¹Assume all the characters in passcode are different, and the same for codeentered: a, a, b, b would not be valid.